

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A method, for interconnecting a Multiplex Section Shared Protection ring network with a Subnetwork Connection Protection ring network in a Dual Node and Bridge & Switch-Switch architecture, the method comprising: through
interconnecting a Multiplex Section Shared Protection ring network with a Subnetwork
Connection Protection ring network via a primary interconnection node and a
secondary interconnection node connected by an optical-fiber span, wherein said
primary interconnection node comprising comprises a means for performing a
Drop & Continue operation, and a-only one Service Selector; and for each circuit,
wherein the method comprises the step of:
closing said Subnetwork Connection Protection ring network through the Service
Selector of the primary interconnection node of the Multiplex Section Shared
Protection ring network, wherein said primary interconnection node is free of a
path selector.
2. (currently amended): A method according to claim 1, wherein ~~said step of closing~~
said Subnetwork Connection Protection ring network through the Service Selector of the primary
node ~~comprises the steps~~, carried out in the primary interconnection node, ~~of~~ comprises:

receiving a signal entering the Multiplex Section Shared Protection ring network,
dropping it towards said Subnetwork Connection Protection ring network and
continuing it towards said secondary interconnection node by utilizing an optical
fiber span connecting said primary and secondary nodes;
selecting one signal, by means of said Service Selector, between
a signal coming from said Subnetwork Connection Protection ring network and
directly entering the primary node and
a signal coming from said Subnetwork Connection Protection ring network,
passed through the secondary node, and entering the primary node by
travelling down an optical-fiber span that connects the primary and
secondary nodes; and
sending said signal that has been selected by the Service Selector to the destination node
of the Multiplex Section Shared Protection ring network.

3. (currently amended): A network element for interconnecting a Multiplex Section
Shared Protection ring network and a Subnetwork Connection Protection ring network in a Dual
Node and Bridge & Switch architecture, said Dual n Node comprising a comprises only one
Service Selector ~~for each circuit~~, wherein said Service Selector
selects one signal between:

a signal coming from said Subnetwork Connection Protection ring network and
directly entering ~~the~~ a primary node, and

a signal coming from said Subnetwork Connection Protection ring network,
passed through ~~said a~~ secondary node, and entering said primary node by
travelling down an optical-fiber span that connects the primary and
secondary nodes;[[,]] and
sends said selected signal to the destination node of the Multiplex Section Shared
Protection ring network, wherein said Dual Node is free of a path selector.

4. (currently amended): A computer program comprising code adapted to perform
~~all of said steps of~~ the method of claim 2, when said program is run on a computer.

5. (currently amended): A computer-readable medium having a program recorded
thereon, said computer-readable medium comprising code adapted to perform ~~all of said steps of~~
the method of claim 2 when said program is run on a computer.